

Speed-E Connect™ 4-port System

Revolutionary Float Switch Connection System Saves Installers Time and Money

INSTALLATION AS EASY AS 1, 2, 3...

1. Mount manifold
2. Plug in float switches
3. Wire manifold cable to panel

Quick release float switch connections allow for easy maintenance and replacement of 1-4 floats, saving installers time and money.

The Speed-E Connect™ 4-port system includes: (a) manifold and (b) mounting bracket. Ordered separately: (c) sealing plug with rubber boot and (d) Speed-E Connect™ low current float switch. 3-port manifold and many float switch options are available to suit your needs!

- **Speed-E Connect™ 4-port manifold features:**
 - (4) Quick release float switch connections
 - A single multi-conductor direct burial cable with colored wire pairs for easy and clean field wiring of control panel
 - Manifold housing includes colored caps that match Red-Blue-Yellow-White wire pairs in manifold cable for easy wiring and identification
 - Can be used with 1, 2, 3, or 4 float switches
 - Stainless steel mounting bracket
- A rubber boot is provided with each float switch for extra protection
- Sealing plug available for unused manifold port(s)
- Use with Speed-E Connect™ mechanically-activated float switches; rated at 125 VAC, 0.160mA to 1A for low current applications; available in multiple configurations (must be ordered separately)
- Rated for short term submersion in water



US Patent No.
9,559,455 and 9,583,867
Foreign Patents Pending

| Part No. | Description |
|-----------|---|
| 1053981 | SPEED-E CONNECT™, 25 ft., with mounting bracket |
| 1053982 | SPEED-E CONNECT™, 50 ft., with mounting bracket |
| 1053983 | SPEED-E CONNECT™, 100 ft., with mounting bracket |
| 1052772* | Sealing plug (includes rubber boot) |
| 1052773** | SPEED-E CONNECT™, 10 ft. cable, narrow-angle, pipe clamp, normally open |
| 1053836** | SPEED-E CONNECT™, 10 ft. cable, narrow-angle, cable weight, normally open |

* One sealing plug kit must be ordered for each unused port.
Do not install with open ports.

** Other Speed-E Connect™ float switch configurations available.

CSI controls®

Toll Free: 1-800-363-5842
Phone: 419-281-5767 • Fax: 419-289-2535
www.csicontrols.com

9500260A ©CSI Controls 08/17

