

Control Duty Narrow-Angle Low Current Mechanical

Low Current Mechanically-Activated, Narrow-Angle Float Switch

Mechanically-activated control switch designed to activate low current control panels and alarms.

This wide-angle or narrow-angle control switch offers reliable low current control for AC and DC applications in water, wastewater, and sewage. The internal switching mechanism has sealed gold cross-point contacts for reliable low current operation. Common applications include PLC (programmable logic controller) panels, IS panels with intrinsically safe barriers, low current solar applications, and other low current control panels and alarms applications.

The wide-angle version activates/deactivates approximately 4" (10.16 cm) above and below horizontal with a 3.5" (9 cm) tether. The narrow angle version activates/deactivates at approximately 1.5" (3.81 cm) above and below horizontal with a 3.5" (9 cm) tether. It is not sensitive to rotation.

Normally Open Model (high level)

The control switch turns on (closes) when the switch tips **above** horizontal signaling a high level, and turns off (opens) when the switch drops below horizontal.

Normally Closed Model (low level)

The control switch turns on (closes) when the switch drops **below** horizontal signaling a low level, and turns off (opens) when the switch tips above horizontal.

FEATURES

- Low current, non-arching applications down to 0.160 mA at 125 VAC
- Mechanically-activated, snap action contacts
- High impact, corrosion resistant polypropylene float housing
- Not sensitive to rotation
- Blue colored cap for easy identification of control switch

OPTIONS

This switch is available:

- for normally open (high level) applications or normally closed (low level) applications
- with narrow or wide-angle pumping ranges
- in standard cable lengths of 15, 20, or 30 feet and 5, 6, or 10 meters (longer lengths available)
- with two mounting options that allow for flexibility in installation:

Mounting Clamp: for applications where the switch can be attached to a discharge pipe or similar mounting device

Externally Weighted: for applications where the switch can be suspended from above



CSI Controls™

Toll Free: 800-363-5842 • Fax: 419-289-2535
customer.service@sjeinc.com
www.csicontrols.com

CONTROL DUTY NARROW-ANGLE LOW CURRENT MECHANICAL CONTROL SWITCH

Normally Open		Normally Closed		Shipping Weight
Part #	Description	Part #	Description	
1031500	15CSLPCNO	1031501	15CSLPCNC	1.37 lbs.
1031502	15CSLCWENO	1031503	15CSLCWENC	2.45 lbs.
1031504	20CSLPCNO	1031505	20CSLPCNC	1.69 lbs.
1031506	20CSLCWENO	1031507	20CSLCWENC	2.70 lbs.
1031508	30CSLPCNO	1031509	30CSLPCNC	2.34 lbs.
1031510	30CSLCWENO	1031511	30CSLCWENC	3.43 lbs.

CS = Control Switch LC = Low Current PC = Pipe Clamp WE = Weighted Externally NO = Normally Open NC = Normally Closed

NOTE: Descriptions are grouped by cable length measured in feet (15, 20, 30).

SEE PRICE BOOK FOR LIST PRICE.

SPECIFICATIONS

CABLE: flexible 18 gauge, 2 conductor (UL, CSA) SJOW, water-resistant (CPE) jacket

FLOAT: 2.74 inch diameter x 4.83 inch long (7.0 cm x 12.3 cm), high impact, corrosion resistant, polypropylene housing for use in sewage and water up to 140°F (60°C)

MAXIMUM WATER DEPTH: 30 feet (9 meters), 13 psi

ELECTRICAL:

125 VAC

Maximum Electrical Load:

1 amp

Minimum Electrical Load:

0.160 milliamps

30 VDC

Maximum Electrical Load:

0.1 amps

Minimum Electrical Load:

0.160 milliamps

5 VDC

Minimum Electrical Load:

1 milliamps

OPTIONS

PACKAGING

Bagged - standard

Boxed - optional

Bulk - optional

ADDITIONAL CABLE

Longer cable lengths available.

Please call for details.

OTHER INFORMATION

NORMALLY OPEN

(HIGH LEVEL) OPERATION

The control switch closes (turns on) when the float tips **above** horizontal signaling a high level, and opens (turns off) when the float drops **below** normal.

NORMALLY CLOSED

(LOW LEVEL) OPERATION

The control switch closes (turns on) when the float drops **below** horizontal signaling a low level, and opens (turns off) when the float tips **above** horizontal.



Toll Free: 800-363-5842 • Fax: 419-289-2535

customer.service@sjeinc.com

www.csicontrols.com

9500376A 10/18

© 2018 SJE, Inc. All Rights Reserved.
CSI CONTROLS is a trademark of SJE, Inc.