

Control Duty Narrow-Angle Mini Mercury

Mercury-Activated, Narrow-Angle Float Switch

Mercury-activated, narrow-angle float switch designed to activate pump control panels and alarms.

This narrow-angle sensing device is used to accurately monitor liquid levels in confined sewage and non-potable water applications. The **Control Duty Narrow Angle Mini Mercury** control switch is not sensitive to rotation.

Normally Open Model (high level)

The control switch turns on (closes) when the switch tips slightly **above** horizontal signaling a high level, and turns off (opens) when the switch drops slightly below horizontal.

Normally Closed Model (low level)

The control switch turns on (closes) when the switch drops slightly **below** horizontal signaling a low level, and turns off (opens) when the switch tips slightly above horizontal.

Contact CSI Controls regarding intrinsically safe applications.

FEATURES

- Designed for use in confined spaces
- Not sensitive to rotation
- Control differential of .5 inches (1 cm) above or below horizontal

OPTIONS

This switch is available:

- for normally open (high level) applications or normally closed (low level) applications
- in standard cable lengths of 15, 20, or 30 feet and 5, 6, or 10 meters (longer lengths available)
- with two mounting options that allow for flexibility in installation:

Mounting Clamp: for applications where the switch can be attached to a discharge pipe or similar mounting device

Externally Weighted: for applications where the switch can be suspended from above



CSI Controls®

Toll Free: 888-342-5753
customer.service@sjeinc.com
www.csicontrols.com

CONTROL DUTY NARROW-ANGLE MINI MERCURY CONTROL SWITCH

Normally Open		Normally Closed		Shipping Weight
Part #	Description	Part #	Description	
1032530	15CSMVNO	1032534	15CSMVNC	1.57 lbs.
1032531	20CSMVNO	1032535	20CSMVNC	1.90 lbs.
1032532	30CSMVNO	1032536	30CSMVNC	2.68 lbs.

CS = Control Switch V = Mercury PC = Pipe Clamp NO = Normally Open NC = Normally Closed

NOTE: Descriptions are by cable length measured in feet.

SEE PRICE BOOK FOR LIST PRICE.

SPECIFICATIONS

CABLE: flexible 18 gauge, 2 conductor (UL, CSA) SJOW, water-resistant (CPE) jacket

FLOAT: 2.81 inch diameter x 3.42 inch long (7.14 cm x 8.68 cm), high impact, corrosion resistant PVC housing for use in sewage and non-potable water up to 140°F (60°C)

MAXIMUM WATER DEPTH: 30 feet (9 meters), 13 psi

MERCURY TILT SWITCH: single pole, single throw, mercury-to-metal contacts, hermetically sealed in a steel capsule and epoxy sealed in the float housing

ELECTRICAL: 5 amp 115/230 VAC, 50/60 Hz

This switch is not recommended for controlling:

- electric loads less than 30 milliamps, 12 VAC
- non-arcing electric loads

NOTE: Contact CSI Controls regarding intrinsically safe applications.

OPTIONS

PACKAGING

Bagged - standard

Boxed - optional

Bulk - optional; must be ordered in master carton quantities.

Please contact customer service for details/pricing.

ADDITIONAL CABLE

Longer cable lengths available. Please call for details.

OTHER INFORMATION

NORMALLY OPEN (HIGH LEVEL) OPERATION

Blue colored cap, the control switch turns on (closes) when the switch tips above horizontal signaling a high level, and turns off (opens) when the switch drops below horizontal.

NORMALLY CLOSED (LOW LEVEL) OPERATION

Red colored cap, the control switch turns on (closes) when the switch drops below horizontal signaling a low level, and turns off (opens) when the switch tips above horizontal.



Toll Free: 888-342-5753
customer.service@sjeinc.com
www.csicontrols.com