

Medium Duty Wide-Angle Mechanical

Mechanically-Activated, Wide-Angle Pump Switch

Mechanically-activated, wide-angle switch specifically designed as a mechanical alternative to the mercury-activated Medium Duty Wide Angle Mini Mercury pump switch.

This mechanically-activated, wide-angle pump switch provides automatic control of pumps in:

- Water
- Sewage applications

This pump switch is not sensitive to rotation or turbulence allowing it to be used in both calm and turbulent applications.

FEATURES

- Mechanically-activated, snap action contacts
- High impact, corrosion resistant, polypropylene float housing
- Adjustable pump range of 8 to 36 inches (20 to 91 cm)

OPTIONS

This switch is available:



- for pump down or pump applications as specified by part number
- with a 125 VAC or 250 VAC piggy back plug
- without a plug for direct wiring in 125 VAC or 250 VAC applications
- in standard cable lengths of 15, 20, or 30 feet and 5, 6, or 10 meters (longer lengths available)



CSI Controls®

Toll Free: 888-342-5753
customer.service@sjeinc.com
www.csicontrols.com

MEDIUM DUTY WIDE-ANGLE MECHANICAL PUMP SWITCH

| Pump Down  | | Pump Up  | | Shipping Weight |
|---|-------------|---|-------------|-----------------|
| Part # | Description | Part # | Description | |
| 1031516 | 15PSD1WP | 1031517 | 15PSU1WP | 1.81 lbs. |
| 1031518 | 15PSDWOP | 1031519 | 15PSUWOP | 1.37 lbs. |
| 1031520 | 20PSD1WP | 1031521 | 20PSU1WP | 2.14 lbs. |
| 1031522 | 20PSDWOP | 1031523 | 20PSUWOP | 1.69 lbs. |
| 1031524 | 30PSD1WP | 1031525 | 30PSU1WP | 2.86 lbs. |
| 1031526 | 30PSDWOP | 1031527 | 30PSUWOP | 2.34 lbs. |

PS = Pump Switch D = Pump Down U = Pump Up 1 = 125 VAC WP = With Plug WOP = With Out Plug

NOTE: Descriptions are grouped by cable length measured in feet (15, 20, 30).

SEE PRICE BOOK FOR LIST PRICE.

SPECIFICATIONS

PUMPING RANGE: 8 to 36 inches (20 cm to 91 cm).

CABLE : flexible 16 gauge, 2 conductor (UL, CSA) SJOW, water-resistant (CPE)

FLOAT: 2.74 inch diameter x 4.83 inch long (7.0 cm x 12.3 cm), high impact, corrosion resistant, polypropylene housing for use in water up to 140°F (60°C)

MAXIMUM WATER DEPTH: 33 feet (10 meters) or 13 psi (90 kPa)

ELECTRICAL:

| Voltage 50Hz/60Hz Single Phase | Max. Pump Run Current | Max. Pump Start Current |
|-----------------------------------|--------------------------|----------------------------|
| 125 VAC | 13 amps | 78 amps |
| 250 VAC | 12 amps | 72 amps |

NOTE: This switch is not recommended for controlling:

- electric loads less than 100 milliamps, 12 VAC
- non-arcing electric loads

NOTE: This switch must be used with pumps that provide integral thermal overload protection.

OPTIONS

MOUNTING CLAMP

is standard - deduct optional

PACKAGING

Boxed - standard

Bagged - optional

Bulk - optional; must be ordered in master carton quantities.

Please contact customer service for details/pricing.

ADDITIONAL CABLE

Longer cable lengths available. Please call for details.

OTHER INFORMATION

PUMP DOWN is normally open contacts for emptying in water or sewage applications.

PUMP UP is normally closed contacts for filling in water or sewage applications.

DIRECT WIRING

Units used for direct wiring (without plug) may be used in 125 VAC or 250 VAC applications within specified amp ratings.



Toll Free: 888-342-5753
customer.service@sjeinc.com
www.csicontrols.com