# Float Accessories

Cable Weight, Cable Clamp Assembly, Float Bracket, Pipe Mounting Bracket, Vertical Reed Switch, Elapsed Time Meter

CABLE WEIGHT

- Provides accurate pivot point for suspended float switches
- Clips to cable

CABLE CLAMP ASSEMBLY

- Includes cable clamp and stainless hose clamp for anchoring float cable.
- Secures 18/16 gauge, 14 gauge and 12 gauge cable in vertical direction

FLOAT BRACKET

- Six Float Bracket supports 1-6 floats
- Four Float Bracket supports 1-4 floats
- Can be directly mounted to wall or used with wall mounting device
- Provides convenient location to stow excess float cord
- Supplied with UL Recognized cord strain relief connectors

PIPE MOUNTING BRACKET

- Secures discharge pipe to basin wall
- Clamps directly to 2" PVC discharge pipe

VERTICAL REED SWITCH

- Control differential: .375 inch (1 cm)
- Maximum angle from vertical: 5°
- Electrical: 250 mAmps, 12-125 VAC, 50/60 Hz

  500 mAmps, 6-12 VDC, 50/60 Hz

ELAPSED TIME METER

- Plugs into switched outlet or piggy-back switch of plugger control panel. Unit must be placed inside an enclosure
- Screws and mounting adhesive included

CSI Controls®

Toll Free: 888-342-5753
customer.service@sjeinc.com
www.csicontrols.com

E.5

FLOAT ACCESSORIES

Cable Weight

Part#	Description
1002230	Cable Weight

HOUSING: 1 pound, 5 ounce (0.6 kgs.), 2.8 inch diameter x 3.3 inch long (7.1 cm diameter x 8.4 cm), impact resistant, non-corrosive, PVC housing for use in liquids up to 140°F (60°C).

CLIP: injection molded acetal plastic

WIRE/CABLE ACCOMMODATED: SJOW, SJTW, 18/2, 18/3, 16/2, 16/3, 14/2 and 14/3

SHIP WEIGHT: 1.6 lbs. (.726 kgs)

Cable Clamp Assembly

Part#	Description
1008569	18 & 16 Gauge Cable Clamp Assembly
1008574	14 Gauge Cable Clamp Assembly
1008575	12 Gauge Cable Clamp Assembly

MOUNTING CLAMP: ABS Nylon blend

HOSE CLAMP: Highly corrosion resistant stainless steel

Float Bracket

Part#	Description
1009432	4 Float Bracket with Mounting Device
1009433	4 Float Bracket without Mounting Device
1009434	6 Float Bracket with Mounting Device
1009435	6 Float Bracket without Mounting Device
1009436	Float Bracket Mounting Device
1027830	304 Stainless Steel Float Bracket with 3 Black Cord Snubbers
1027647	304 Stainless Steel Float Bracket with 4 Black Cord Snubbers

METAL COMPONENTS: all metal components are made of 300 series stainless steel

STRAIN RELIEF CONNECTORS: which accommodate 18/2, 18/3, 16/2, 16/3 SJOW and SJTW cords

Pipe Mounting Bracket

Part#	Description
1027771	Pipe Mounting Bracket

Vertical Reed Switch

Part#	Description
1032426	15CSRS1

HOUSING AND FLOAT: 1.60 inch diameter x 6.7 inch long (4.06 cm X 17.01 cm), high impact, corrosion resistant PVC for use in sewage and non-potable water up to 120°F (50°C)

Elapsed Time Meter

Part#	Description
1022846	ETM with 120V Piggy-Back Plug
1032834	ETM with 230V Piggy-Back Plug

CSI Controls.

California Prop 65 requires the following: ⚠ WARNING Cancer and Reproductive Harm – www.P65Warnings.ca.gov